



# LED Beveled Retrofit CCT Selectable Downlights

## Product Specifications



TCP's LED Beveled Retrofit CCT Selectable Downlights are the perfect choice for remodeling or new construction projects. The slim, energy-efficient design is easy to install and offers a rated lifetime of 50,000 hours.

## Reasons to choose the LED Beveled Retrofit CCT Selectable Downlights from TCP

- Mounts directly to recessed can (4", 5", or 6") for easy installation with integrated trim, including pigtail and spring clips
- Excellent color consistency
- Easy installation
- Dimmable
- Slim, low-profile design
- Selectable CCT (27K/30K/35K) or (30K/40K/50K)
- 50,000 hours rated life
- Back-lit technology
- 4" models UL approved for damp locations; 5"/6" models UL approved for wet locations
- IC rated

## Ideal Applications

- Retrofits
- New construction
- Residential
- Office
- Retail
- Hospitality
- Drop ceilings
- Remodeling



## Applications

Perfect for dimmable downlight applications in retrofit or new construction applications.

## Construction

Mounts directly to recessed can (4" or 5"/6") with integrated trim for easy installation, including pigtail and spring clips.

## Electrical

- 4" models UL approved for damp locations
- 5"/6" models UL approved for wet locations
- Easy installation with integrated E26 base adapter
- 50,000 hours rated life

## Optics

- Excellent color consistency
- Smooth, uniform dimming
- Highly-efficient LEDs and driver
- Triac dimming



### Listings

cULus Listed, RoHS

### Warranty

Five year limited warranty against defects in manufacturing.

## LED Beveled Retrofit CCT Selectable Downlights

ITEM #	DESCRIPTION	VOLTAGE	INCAND. WATTS	WATTAGE	LUMENS	LPW	CCT SELECTABLE	CRI	BEAM ANGLE	MOL (IN)	DIAMETER (IN)
LEDDR4BVCCT1	4" BEVELED RETROFIT CCT 27/30/35	120	75	10.5	700	66.7	27K/30K/35K	80	100°	1.5	5
LEDDR4BVCCT2	4" BEVELED RETROFIT CCT 30/40/50	120	75	10.5	700	66.7	30K/40K/50K	80	100°	1.5	5
LDR56BVCCT1	5"/6" BEVELED RETROFIT CCT 27/30/35	120	85	16	1400	87.5	27K/30K/35K	80	90°	1.5	7.4
LDR56BVCCT2	5"/6" BEVELED RETROFIT CCT 30/40/50	120	85	16	1400	87.5	30K/40K/50K	80	90°	1.5	7.4

TCP Standard LED Lamps, LED Filament Lamps and TCP Downlights have been tested to work with the following dimmers:

BRAND	MODEL
LUTRON	AYCL-153P
	CTCL-153PD-H
	CTCL-53PD-H
	DV-600P
	DV-600PR-WH
	DV-603PH-WH
	DVCL-153P
	LGCL-153P
	MACL_153M
	MSCL-OP153M
	PD-6WCL
	SCL-153PR
	SELV-300P
	TGCL-153P
	MRF2S-6ELV120-WH
LEVITON	6811
	6602
	6631
	6672
	6672-L
	6674
	DSLO6
	IPL06
COOPER	DAL06P
	SAL06P

\*Dimming compatibility tests are performed under a controlled lab environment. Field conditions may vary from this type of environment. Dimmers may differ by age and versions under the same item number which may affect compatibility. Compatibility may also extend beyond this list as TCP products should work with most C-L Type Triac Dimmers. TCP recommends trying a few dimmer-lamp combinations in an on-site test to ensure compatibility and performance before a major installation. If there's a dimmer not on this list we can perform a lab test for compatibility.

# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcp.com](http://tcp.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516